GLASS-LOOK DOOR
HIGH SPEED ALUMINIUM ROLL UP DOOR

High Speed Door for interior & exterior applications

HIGH TECH ROLL UP FAST & FASHION DOOR | TECHNICAL SPECIFICATIONS

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- Glass-look 90% clear vision made of polycarbon
- Patented rubber drive method

Door Type			Roll-up
Use	Internal / External Door		Standard
Door Sizes	Max Width Max Height		4000 mm 5000 mm
Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking Opening Speed up to Closing Speed		 2,0 m/s 0.7 m/s
Security Features	EN 13241-1		Standard
Resistance to Wind Load	EN 12424		up to Class 2
Door Leaf Material / Surface	Aluminium Anodized polycarbon windows RAL 9006 aluminium inside polycarbon		Standard Standard
Guide Material / Surface	Aluminium Anodized Painting in any RAL color		Standard Optional
Shaft / Operator Cover	Straight		Optional
Operator and Control (German brand)	Connecting Voltage	1-phase 3-phase	220V - 1 ph, N 380V - 3 ph, N
	Open-Stop-Close Button		Standard
	Protection Category (Operator / Control)		IP 54 / IP 65
	Emergency-OFF Button		Standard
	Closing Zone Monitoring	Light Grille IP 67	Standard
	External Route Monitoring	Photocell	Optional
	Door area Monitoring	Radar Presence Detector Induction Loop	Optional Optional
	Electronic Limit Switch		Standard
Emergency Opening	Crank Handle Chain		Standard Optional
Standard Curtain Colours	White Similar to RAL 9016 Ivory Similar to RAL 1015 Light beige	Brown Similar to RAL 8014 Green Similar to RAL 6005 Anthracite grey Similar to RAL 7016	